

Hydraulic Transport Boxes

Hydraulic Compact Transport Boxes (HYD4C, HYD5C)



- Suitable for all compact and sub compact tractors
- Solid construction of reinforced 3mm steel plate
- Robust hydraulic loading & tipping hitch mechanism
- Heavy duty double acting ram
- Requires double acting spool valve
- Range of 3PL settings to suit most tractors
- Double jaw lift arm pin support
- Cat 1 Pins supplied
- Internal reinforcing shoes tie the strength of the floor to the cross beams on the back of the box creating a solid back plate to absorb the force of the tractor. The reinforcing shoes have smooth rounded edges for easy unloading and cleaning
- The heel of the box is fitted with a scraping blade, supported by the floor skids further adding reinforcing strength to the back of the box and giving the capability of grading and levelling stones, sand, soil ,etc.



Code	Weight (kg)	Width (mm)	Height (mm)	Depth (mm)	Capacity (cu.m)	Max H.P	Body Material (mm)	Lift Pin
HYD4C	129	1260	510	640	.34	50	3	cat.1
HYD5C	140	1510	510	640	.43	55	3	cat.1

Hydraulic Transport Boxes

Hydraulic Transport Boxes



- To suit tractors from 60–130 Horse Power
- Solid construction of reinforced steel plate
- Heavy duty hydraulic loading & tipping hitch mechanism.
- Heavy duty double acting ram.
- Requires double acting spool valve.
- Reinforced floor and nose plate for loading and scraping.
- Range of 3PL settings to suit most tractors
- Double jaw lift arm pin support
- Cat 2 lift arm pins.
- Internal reinforcing shoes tie the strength of the floor to the cross beams on the back of the box creating a solid back plate to absorb the force of high horse power tractors.
- The 5mm thick folded form of the box has 2 internal reinforcing beams across the back of the body eliminating any flexing when the box is under heavy load. The heel of the box is fitted with a scraping blade, supported by the floor skids further adding reinforcing strength to the back of the box and giving the capability of grading and levelling stones, sand, soil ,etc.



Code	Weight (kg)	Width (mm)	Height (mm)	Depth (mm)	Capacity (cu.m)	Max H.P	Body Material (mm)	Lift Pin
HYD5	267	1510	610	930	.54	80	5	cat.2
HYD6	296	1830	610	930	.66	100	5	cat.2
HYD66	311	2000	610	930	.72	100	5	cat.2
HYD7	380	2170	610	930	.78	130	6	cat.2