

indespension

Plant Trailer Specifications



**We are in the
places you are!**



**We have a nationwide retail network across the
UK and Ireland:**

Belfast	02890 839 933	belfast@indespension.co.uk
Bolton	01204 397 999	bolton@indespension.co.uk
Cardiff	02920 359 073	cardiff@indespension.co.uk
Carlisle	01228 525 821	carlisle@indespension.co.uk
Derby	01332 348 555	derby@indespension.co.uk
Dublin	01 808 1300	dublin@indespension.com
Edinburgh	0131 6 617 571	edinburgh@indespension.co.uk
Gatwick	01293 526 300	gatwick@indespension.co.uk
Glasgow	0141 9563 055	glasgow@indespension.co.uk
Ipswich	01473 749 922	ipswich@indespension.co.uk
Lancaster	01524 383 666	lancaster@indespension.co.uk
Leeds	0113 2707 444	leeds@indespension.co.uk
Limerick	061 225700	limerick@indespension.com
Newcastle	0191 2530 411	newcastle@indespension.co.uk
Northampton	01604 875 126	northampton@indespension.co.uk
Portsmouth	02392 267 955	portsmouth@indespension.co.uk
Swansea	01792 793 496	swansea@indespension.co.uk
West Midlands	0121 5615 467	westmidlands@indespension.co.uk
Central Sales	01204 478 591	centralsales@indespension.co.uk

indespension.co.uk

Indespension is your number one choice for plant trailers, from our industry leading AD range to the super light-weight Alumax we have a trailer that is right for the job. All of our plant trailers are fitted with seal for life bearings and hot dipped galvanised chassis for strength and durability.

The Alumax is an industry leading trailer with a payload of 2,910kg. It is fitted with aluminium decks and ramps, and has a low bed height and loading angle. The Beavertail trailers are fitted with ALKO industry leading brakes and the AD Range have a chassis tread plate construction and dual voltage LED lights.

Please note, premium options and additional parts such as deck rings or a spare wheel will alter the gross weight, unladen weight and payload of your trailer.

		CHALLENGER 50 BEAVERTAIL RANGE			AD RANGE			
		<u>AD27094BTS</u>	<u>AD35105BTS</u>	<u>AD35126BTS</u>	<u>AD2000</u>	<u>AD2800SPLED</u>	<u>ALUMAX</u>	
SPECIFICATION	Gross Weight	kg	2700	3500	3500	2700	3500	3500
	Unladen Weight	kg	570	745	815	540	760	590
	Payload	kg	2130	2755	2685	2160	2740	2910
	Internal Dimensions LxWxH	m	2.78 x 1.26	3.04 x 1.68	3.65 x 1.83	2.49 x 1.26	3.05 x 1.80	3.05 x 1.70
		ft x ins	9'1" x 4'1"	10' x 5'6"	12' x 6'	8'2" x 4'1½"	10'1" x 5'11"	10' x 5'7"
	Bed Height		430	430	430	404	456	367
	Studding		5 X M16 on 165.1mm PCD	5 X M16 on 165.1mm PCD	5 X M16 on 165.1mm PCD	5 X M16 on 165.1mm PCD	5 X M16 on 165.1mm PCD	5 X M16 on 165.1mm PCD
	Standard Ramp Dimensions	mm	1450 x 1208	1450 x 1630	1450 x 178	1290 x 1237	1500 x 1790	1330 x 400 Ea.
	Standard Ramp Angle		13°	13°	13°	N/A	17°	15.5°
Spring Ramp Angle		N/A	N/A	N/A	17°	17°	N/A	
Tyre Size		165 R13C	185/70 R13C	185/70 R13C	165 R13C	185/70 R13C	185/70 R13C	

[View the range here](#)