

GRASS CARE

Toppers and Roller Mowers

Teagle



teagle.co.uk



GRASS CARE

Toppers and Roller Mowers



DYNAMO 6/8

Roller Mowers • Pg 3

W/Widths 1.83m/2.44m



TOPPER 4/5/510

Single Rotor • Pg 5

W/Widths 1.22m / 1.52m / 1.78m



TOPPER 6/8

Twin Rotor • Pg 6

W/Widths 1.83m/2.44m



Teagle Machinery, founded in 1937, has forged a global reputation as a market leading producer of quality farm machinery. We remain a family-owned business focussed on meeting the needs of our customers whether just around the corner, or in one of the 35 countries worldwide to which we regularly ship our machinery.

From the outset, our machinery has been designed to be simple, robust and easy to use. We still stand by these values and all of our products are tested extensively on farms throughout the world to ensure that they perform reliably day-in and day-out under the toughest conditions.

As sales of our popular range of Toppers and Roller Mowers continue to grow, we believe that the reasons that customers return to us time after time are twofold:

Product Focus - We actively invest in research, design and manufacturing technology to ensure that our product range constantly evolves to remain at the cutting edge, whilst being available at a competitive price. Our range of Toppers and Roller Mowers are based on a strong, robust body, with high quality gearboxes and sprung steel cutting blades. The powder coat paint application creates a durable, high-quality finish.

Backup - Aftersales support is our priority, requiring commitment to a comprehensive parts stock, an experienced team of Area Managers and an effective dealer network. Part of our 25,000m² facility in Cornwall is dedicated to a substantial stock of wearing and non-wearing parts to keep you up and running.



TOPPER 8 OFFSET

Twin Rotor • Pg 7
W/Width 2.44m



TOPPER 9

Twin Rotor • Pg 8
W/Width 2.74m

Teagle

British Built & Backed

Build quality that ticks all the boxes



✓ Strength

Advanced construction incorporating high strength pressings ensure in-built strength.

✓ Durability

All machines manufactured at our factory in Cornwall are shot blasted and finished with a durable powder coat paint.

✓ Support

To keep your Topper running Teagle carry a comprehensive stock of spare parts for next day delivery.



Dynamo 6 / 8 Roller Mowers



Cutting width

1.83m - 2.44m

HP

25-45




PTO

540rpm



Roller Mowers

SUITABLE FOR: Parks, Golf Courses, Sports Pitches, Playing Fields, Leisure Areas and Amenity applications.



MODEL	A	B	Cutting Height	Rotor	min	Weight	Linkage	PTO
6	1.96m	1.83m*	12-100 mm	2	25	380 kg	Cat 1 & 2	540rpm
8	2.54m	2.44m*	12-100 mm	2	45	485 kg	Cat 2	540rpm

Front Roller	<input type="radio"/>	Hydraulic Offset Kit	<input type="radio"/>	Mulching Kit	<input type="radio"/>
Overrun PTO Shaft	<input type="radio"/>	Driveline Protection	<input checked="" type="radio"/>	Height Control	<input checked="" type="radio"/>

*Cutting width

Key: = Optional = Standard N/A = Not Applicable

Features

Find out why operators return again and again to the market leading range of Teagle Toppers and Roller Mowers



(Dynamo 8 Roller Mower Pictured)



Full Width Coverage

Twin rotor models have offset rotors to ensure blade overlap.



Spread Cut Material

A rotor divider and deflector deliver an even spread of cut material across the width of the mower.



Reduced Wheel Marks

Sliding offset comes as standard on Topper/ Dynamo 6 & 8.



Height Control

Bolted adjustment for toppers and jacking screw for fine adjustment on roller mowers.



Pivoting Headstock

A pivoting headstock ensures the topper follows ground contours



In-Built Strength

High strength pressings are incorporated into all of our Topper bodies for a robust, durable product.



A Clean Cut

The smooth underside assists the flow of cut material through the machine.



Driveline Protection

Features shear bolts on the PTO with either belt drive transmission or flexible drive couplings.

The Cutting Edge...



Hardened spring steel blades rotate on hardened bushes to reduce likelihood of stone damage, and are mounted on spring steel blade holders.





Cutting width	HP	PTO
1.22m - 1.90m	12-25	540rpm



Single Rotor Toppers

SUITABLE FOR: Smaller Agricultural Areas, Parks, Playing Fields and Leisure Areas.



MODEL	A	B	Cutting Height	Rotor	min	Weight	Linkage	PTO
4	1.36m	1.22m*	12-130 mm	1	12	170 kg	Cat 1	540rpm
5	1.64m	1.64m*	12-130 mm	1	20	213 kg	Cat 1	540rpm
510	1.98m	1.90m*	25-150 mm	1	25	290 kg	Cat 1 & 2	540rpm

Overrun PTO Shaft	<input type="radio"/>	Height Control	<input checked="" type="radio"/>	Mulching Kit	N/A
-------------------	-----------------------	----------------	----------------------------------	--------------	-----

* Cutting width

Key: = Optional = Standard N/A = Not Applicable

Topper 6 / 8






Cutting Width	Min HP	PTO
1.83m - 2.44m	25-45	540rpm



Twin Rotor Belt Drive

SUITABLE FOR: Agricultural Pasture, Playing Fields, Leisure Areas and Amenity applications.



MODEL	A	B	Cutting Height	Rotor	Min	Weight	Linkage	PTO
6	1.96m	1.83m*	12-100 mm	2	25	310 kg	Cat 1 & 2	540rpm
8	2.54m	2.44m*	12-100 mm	2	45	410 kg	Cat 2	540rpm

Hydraulic Offset Kit (Topper 6 & 8)	<input type="radio"/>	Overrun PTO Shaft	<input type="radio"/>	Height Control	<input checked="" type="radio"/>
-------------------------------------	-----------------------	-------------------	-----------------------	----------------	----------------------------------

* Cutting width

Key: ○ = Optional ● = Standard N/A = Not Applicable

Topper 8 Offset





Cutting Width	Min HP	PTO
2.40m	80	540rpm



Twin Rotor Offset

SUITABLE FOR: Agricultural Pasture. Say goodbye to wheel marks.



MODEL	A	B	Cutting Height	Rotor	Min	Weight	Linkage	PTO
8 Offset	1.80m**	2.40m*	12-100 mm	2	80	535 kg	Cat 2	540rpm

Overrun PTO Shaft	<input type="radio"/>	Easy Folding for Transport	<input checked="" type="radio"/>	Height Control	<input checked="" type="radio"/>
-------------------	-----------------------	----------------------------	----------------------------------	----------------	----------------------------------

* Cutting width ** Transport Width

Key: = Optional = Standard N/A = Not Applicable


Topper 9



Cutting width	Min HP	PTO
2.74m	55	540rpm

Twin Rotor Shaft Drive

SUITABLE FOR: Agricultural Pasture. Rear mount as standard or front mount for a cleaner cut.



MODEL	A	B	Cutting Height	Rotor	Min	Weight	Linkage	PTO
9	2.84m	2.74m*	12-100 mm	2	55	500 kg	Cat 2	540/1,000rpm**

Overrun PTO Shaft	<input type="radio"/>	Height Control	<input checked="" type="radio"/>	Front Mounting Kit	<input type="radio"/>
-------------------	-----------------------	----------------	----------------------------------	--------------------	-----------------------

* Cutting width ** 1000 rpm must be specified at time of ordering - gear ratios are different

Key: = Optional = Standard N/A = Not Applicable

Flail Mulcher Range

Teagle now offer over 60 different Flail Mulcher models, from a Mini Garden for a 12HP compact tractor through to Forestry Mulchers for tractors up to 300HP.

| Excavator |



| Skid Steer |



| Agricultural |



| Specialist |



| Verge |



| Forestry |



With over 5000 machines working successfully throughout the UK you can be confident in your choice of Teagle Flail Mowers and Mulchers.



VIEW OUR FULL RANGE



Environmental Management comes in many forms and processes. There is a requirement to cultivate species rich habitats in areas that have not been productive farmland. To assist farmers in creating these habitats in and around Rosshire, Agricultural Contractor John Mackenzie has purchased a Teagle EFX/DT 220 Forestry Mulcher equipped with a rigid carbide tooth rotor.

"The Mulcher has to work in some fairly harsh environments and the reliability of the implement has been excellent." states John.

John Mackenzie and Son,
Ross Shire Scotland
Machine; EFX/DT 220



If they give you one on demo, you won't want to give it back!

Here at Kingfisher forestry and moorland we have two TBM/S and a TSB/S these are used for heather, rush, pasture and mulching of crops, the double chop of the Teagle and the large drum capacity leaves a very fine mulch, which is perfect for all applications.

We at Kingfisher have had a good working relationship with Teagle sales, which shows they have confidence in their machines. If they give you one on demo, you won't want to give it back !!

John Drummond,
North Yorkshire
Machine; TBM/S

Teagle

With over 75 years experience in designing and manufacturing agricultural machinery you can be confident when you choose Teagle.

Contact us today to discuss your individual requirements.

**Call our Sales Office:
01872 560592**



Ireland and NI Sales Manager

Frank Byrne +353 (0)871 948404
frank.byrne@teagle.ie

North Manager

Gary Eastham 07866 532666
gary.eastham@teagle.co.uk

South East Manager

Chris White 07970 136614
chris.white@teagle.co.uk

Scotland Manager

David Haggart 07970 136616
david.haggart@teagle.co.uk

West Manager

Steve Offland 07970 462240
steve.offland@teagle.co.uk

South West Manager

Mike Sanders 07970 836705
mike.sanders@teagle.co.uk

View our full range at teagle.co.uk



TOMAHAWK

Bale Processors
Output up to 3.0t/hr



TITAN

Rear Discharge Spreader
Capacity 6.3m³ - 20.1m³



TELEHAWK T2

Hydraulic Straw Bedder
Blow Distance up to 13.5m

Teagle Machinery Ltd Blackwater, Truro, Cornwall TR4 8HQ

sales@teagle.co.uk www.teagle.co.uk Tel: +44 (0)1872 560592  teagle.co.uk

GRASS04BOBBUK